

D-FOAM

| | |
|---------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 0 |
| REACTIVITY: | 0 |

PRECAUTIONS

Do not get in eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

SILICONE BASED DEFOAMER

DIRECTIONS FOR USE

D-FOAM can be used virtually anywhere foam is a problem. It is best to mix 1 part D-FOAM in 2 parts of warm water before adding to the system. This will ensure a quick defoaming action. The amount of D-FOAM required will depend on the system but the initial starting point should be 1 ounce per 50 gallons (0.015%).

STORAGE & DISPOSAL

Keep containers tightly closed when not in use. Empty container completely and dispose of in accordance with applicable regulations. SPILLS: Contain spill. Absorb with inert material and dispose in accordance with applicable regulations. Store away from food production areas and food storage areas.

HEALTH HAZARDS

May cause eye and/or skin irritation. Ingestion may cause discomfort.

FIRST AID

FIRST AID: In case of contact, immediately flush eyes and/or skin with lots of running water for at least 15 minutes while removing contaminated clothing and/or shoes. Get medical attention. Wash clothing before reuse.

CONSULT MSDS FOR FURTHER INFORMATION
KEEP OUT OF REACH OF CHILDREN

WESMAR CO. INC.

5720 204TH ST. SW
LYNNWOOD, WA 98036
(206) 783-5344

| | |
|-----------|--------|
| DATE: | 121411 |
| LOT #: | |
| CONTENTS: | |